

# AGGREGATE MANAGEMENT

Your Guide  
to Profitable  
Production

Randall Reilly

July 2010

[www.AggMan.com](http://www.AggMan.com)

# SPEC GUIDE

**2** Hydraulic  
hammers/breakers

**9** Manufacturer's  
index

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES MANAGER**  
your guide to equipment

**NOMINAL RATINGS**

**CERTIFIED MEASUREMENTS**



Make	Model	Tool diameter (in)	Working weight (lbs)	Model	Manufacturer's recommended carrier size range (lbs)
<b>2,800 to &lt;3,000 lbs working weight</b>					
Maverick	4750	4.7"	2,871	4750	35,000 - 48,000
Stanley	MB40EXS	5"	2,859	MB40EXS	30,000 - 50,000
International Tractor	PM 750	4.70"	2,860	PM 750	35,000 - 62,000
Socomac	MDO 1300	4.7"	2,860	MDO 1300	30,000 - 44,000
International Tractor	ITC190	4.9"	2,865	ITC190	34,000 - 48,000
BTI	BT3500	4.7"	2,867	BT3500	35,000 - 55,000
Caterpillar	H120Cs	4.53"	2,870	H120Cs	37,400 - 57,200
Allied Construction Products	E 66 N/C Sandvik (Rammer)	4.52"	2,900	E 66 N/C Sandvik (Rammer)	40,000 - 57,000
NPK	E-208	4.6"	2,900	E-208	28,000 - 42,000
Komac	TOR-18	4.25"	2,910	TOR-18	37,400 - 50,700
<b>3,000 to &lt;3,500 lbs working weight</b>					
Allied Construction Products	m 14 (BR 2214) Sandvik (Rammer)	4.92"	3,042	m 14 (BR 2214) Sandvik (Rammer)	40,000 - 53,000
FRD Furukawa	KF 19Qt	4.75"	3,090	KF 19Qt	31,000 - 42,000
Allied Construction Products	AR 120B	4.72"	3,201	AR 120B	40,000 - 62,001
Atlas Copco	MB 1500	5.31"	3,310	MB 1500	37,500 - 63,900
Indeco	HP 4000	5.10"	3,320	HP 4000	35,500 - 61,500
UB Equipment	UB-312	5.26"	3,330	UB-312	36,000 - 56,000
Construction Attachments	CAL3200-A	4.92"	3,406	CAL3200-A	32,000 - 44,000
Tramac	V32MS	4.8"	3,408	V32MS	39,700 - 66,150
Tramac	V1200MS	4.8"	3,461	V1200MS	39,700 - 66,150

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES  
MANAGER**  
your guide to aggregates

**NOMINAL RATINGS**  
**CERTIFIED MEASUREMENTS**



Make	Model	Working weight (lbs)	Tool diameter (in)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>3,500 to &lt;4,000 lbs working weight</b>														
Chicago Pneumatic	CP 1650	3,577	5.3"	--	360 - 540	34 - 45	1,740 - 2,030	--	--	--	--	--	39,683 - 74,957	CP 1650
Komac	TOR-23	3,594	5.0"	4,000	400 - 800	33.0 - 39.6	2,321 - 2,611	108"	--	--	--	--	39,500 - 57,500	TOR-23
NPK	GH-9	3,600	5.0"	3,000	500 - 670	40 - 53	2,600	108.75"	--	--	--	--	40,000 - 56,000	GH-9
Okada	Top 200	3,616	4.9"	3,500	465 - 625	31.7 - 42.3	2,030 - 2,620	86.8"	--	--	--	--	32,000 - 48,000	Top 200
Okada	Top 205	3,720	5.3"	4,000	340 - 700	26.5 - 34.4	2,030 - 2,600	88"	--	--	--	--	40,000 - 60,000	Top 205
Allied Construction Products	AR 130B	3,725	5.12"	3,500	350 - 470	32 - 43	1,950 - 2,250	109"	2,400	396	42.9	2,182	44,000 - 76,000	AR 130B
Maverick	5250	3,726	5.3"	4,500	300 - 600	33 - 40	2,320 - 2,610	--	2,334.4	300 - 600	33 - 40	--	38,000 - 54,000	5250
Caterpillar	HT30S	3,740	5.12"	3,500	320 - 560	31 - 53	2,030	89.7"	2,758	--	--	--	41,800 - 70,400	HT30s
Socomac	MDO 1700	3,740	5.3"	6,500	480 - 650	39.0 - 50.0	2,000	108.0"	3,200	650	50.0	2,000	38,000 - 54,000	MDO 1700
Atlas Copco	MB 1700	3,750	5.51"	--	320 - 600	34 - 42	2,320 - 2,610	97.52"	--	--	--	--	39,700 - 75,000	MB 1700
Allied Construction Products	E 68/C Sandvik (Rammer)	3,800	5.12"	3,500	330 - 580	32 - 53	1,960 - 2,100	90"	--	--	--	--	46,000 - 71,000	E 68/C Sandvik (Rammer)
Arrowhead	S230	3,810	5.25"	4,000	400 - 700	39 - 53	1,900	90"	--	--	--	--	40,000 - 61,500	S230
FRD Furukawa	KF 22 Qt	3,812	5.25"	4,000	360 - 700	37 - 48	2,320 - 2,610	105"	2,537	--	--	--	42,000 - 48,000	KF 22 Qt
Maverick	6250	3,924	5.5"	5,500	350 - 500	38 - 48	2,320 - 2,610	--	2,577.0	350 - 500	38 - 48	--	42,000 - 65,000	6250
Stanley	MB50EXS	3,964	5.5"	5,000	400 - 500	32 - 48	2,700	96"	--	--	--	--	41,000 - 65,000	MB50EXS

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES  
MANAGER**  
Your guide to  
equipment

**NOMINAL RATINGS**  
**CERTIFIED MEASUREMENTS**




Make	Model	Working weight (lbs)	Tool diameter (in)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>4,000 to &lt;5,000 lbs working weight</b>														
Okada	Top 210	4,079	5.3"	4,000	310 - 480	31.7 - 42.3	2,030 - 2,600	91.2"	--	--	--	--	40,000 - 60,000	Top 210
Allied Construction Products	m 18 (BR 2518) Sandvik (Rammer)	4,145	5.51"	7,000	450 - 800	43 - 58	2,030 - 2,320	103"	--	--	--	--	46,000 - 71,000	m 18 (BR 2518) Sandvik (Rammer)
Tramac	V1800	4,154	5.5"	6,000	310 - 800	37.0 - 58.2	2,394	100.7"	--	--	--	--	55,100 - 66,150	V1800
Construction Attachments	CAL4500-A	4,180	5.32"	4,500	340 - 800	34.4 - 68.7	1,860 - 2,580	112.0"	--	--	--	--	36,000 - 56,000	CAL4500-A
NPK	GH-10	4,200	5.4"	4,000	400 - 550	44 - 55	2,600	111"	--	--	--	--	46,000 - 66,000	GH-10
FRD Furukawa	KF 27 Qt	4,244	5.51"	5,000	340 - 440	41 - 50	2,320 - 2,610	114"	2,732	--	--	--	48,000 - 57,000	KF 27 Qt
Indeco	HP 5000	4,350	5.55"	5,000	410 - 870	39 - 48	1,850 - 2,150	98.4"	--	--	--	--	42,000 - 70,500	HP 5000
BTI	BT4000	4,441	5.3"	4,000	330 - 530	34 - 45	2,031 - 2,611	111"	--	--	--	--	37,000 - 66,000	BT4000
BTI	VZ50	4,520	5.3"	5,000	480 - 720	42 - 53	2,030 - 2,755	110"	--	--	--	--	39,700 - 88,200	VZ50
Stanley	MB60EXS	4,566	5.9"	6,000	300 - 450	37 - 55	2,700	105"	--	--	--	--	46,000 - 68,000	MB60EXS
Maverick	8250	4,586	5.9"	6,500	450 - 750	42 - 50	2,320 - 2,610	--	3,283.8	450 - 750	42 - 50	--	55,000 - 89,000	8250
Allied Construction Products	AR 140B	4,620	5.51"	5,500	350 - 550	43 - 53	1,890 - 2,030	110"	--	--	--	--	55,000 - 88,000	AR 140B
Surestrike	RC10	4,700	5"	10,000	22	20 - 25	2,700 - 3,000	192"	--	--	--	--	30,000	RC10
Okada	OKB 316	4,740	5.5"	5,000	360 - 700	38.3 - 48.8	1,850 - 2,420	97"	--	--	--	--	44,000 - 66,000	OKB 316
Atlas Copco	HB 2200	4,850	5.91"	--	280 - 550	37 - 47.6	2,320 - 2,610	102.51"	--	--	--	--	57,300 - 88,200	HB 2200
Chicago Pneumatic	CP 2250	4,850	5.9"	--	280 - 550	37 - 48	2,320 - 2,611	--	--	--	--	--	57,320 - 88,185	CP 2250
Komac	TOR-36	4,850	5.71"	5,500	360 - 700	42.3 - 50.2	2,321 - 2,611	122"	--	--	--	--	59,500 - 77,500	TOR-36
Indeco	HP 5500	4,900	5.75"	5,000	390 - 760	43 - 53	1,900 - 2,300	102.6"	--	--	--	--	46,500 - 83,500	HP 5500
UB Equipment	UB-313	4,900	5.46"	5,000	340 - 760	39.6 - 58.1	2,275 - 2,702	--	--	--	--	--	50,000 - 64,000	UB-313
BTI	TB1280XC	4,917	5.5"	5,500	470 - 610	50 - 65	2,030 - 2,755	112.5"	3,459	565	60	2,769	42,000 - 90,000	TB1280XC

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES  
MANAGER**  
Your guide to aggregates

## NOMINAL RATINGS



Make	Model	Working weight (lbs)	Tool diameter (in)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>5,000 to &lt;6,000 lbs working weight</b>														
Socomac	MDO 2300	5,060	6.0"	8,000	460 - 630	51.0 - 59.0	2,000	116.0"	4,400	630	59.0	2,000	50,000 - 66,000	MDO 2300
Caterpillar	H140DS	5,182	5.5"	5,500	350 - 600	42 - 60	2,321	103.9"	3,153	--	--	--	55,000 - 88,000	H140DS
Allied Construction Products	G 88 C Sandvik (Rammer)	5,225	5.59"	5,500	300 - 480	42 - 60	2,030 - 2,180	--	--	--	--	--	59,500 - 88,200	G 88 C Sandvik (Rammer)
International Tractor	ITC450	5,290	5.9"	4,500	300 - 500	42 - 50	2,321 - 2,611	--	--	--	--	--	62,000 - 93,000	ITC450
FRD Furukawa	KF 35Qt	5,328	6"	6,000	320 - 600	48 - 58	2,320 - 2,610	121"	3,299	--	--	--	57,000 - 70,000	KF 35Qt
BTT	BT5500	5,493	5.7"	5,500	300 - 400	42 - 58	2,031 - 2,611	117"	--	--	--	--	49,000 - 84,000	BT5500
Atlas Copco	HB 2500	5,510	6.1"	--	280 - 550	45 - 58	2,320 - 2,610	107.29"	--	--	--	--	59,500 - 101,400	HB 2500
Tramac	V46MS	5,616	5.91"	7,500	345 - 1,160	47.5 - 70.0	2,394	104.6"	--	--	--	--	59,500 - 88,200	V46MS
Allied Construction Products	AR 160C	5,620	6.29"	7,500	300-450	50 - 63	1,900 - 2,200	120"	--	--	--	--	72,000 - 100,000	AR 160C
NPK	GH-12	5,650	5.7"	5,500	380 - 480	45 - 58	2,650	123.25"	--	--	--	--	56,000 - 86,000	GH-12
Tramac	V2500	5,669	6.3"	8,000	350 - 800	46.3 - 66.1	2,250	112.3"	--	--	--	--	59,500 - 88,200	V2500
Construction Attachments	CAL6000-A	5,762	5.90"	6,000	250 - 650	47.6 - 73.9	1,860 - 2,580	120.0"	--	--	--	--	44,000 - 70,000	CAL6000-A
Indeco	HP 7500	5,780	5.95"	7,500	370 - 820	48 - 61	1,900 - 2,300	103.5"	--	--	--	--	51,000 - 92,500	HP 7500
Stanley	MB70EXS	5,803	6.1"	7,500	300 - 400	45 - 63	2,700	110"	--	--	--	--	58,000 - 85,000	MB70EXS
Maverick	9250	5,842	6.3"	8,500	260 - 400	50 - 66	2,275 - 2,702	--	5,471.7	260 - 400	50 - 66	--	70,000 - 105,000	9250

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES MANAGER**  
Your guide to aggregates equipment

**NOMINAL RATINGS**  
**CERTIFIED MEASUREMENTS**



Make	Model	Working weight (lbs)	Tool diameter (in)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>6,000 to &lt;7,000 lbs working weight</b>														
UB Equipment	UB-316	6,272	6.3"	8,000	230 - 470	41.9 - 81.6	2,280 - 3,000	--	--	--	--	--	56,000 - 72,000	UB-316
Stanley	MB80EXS	6,246	6.4"	8,500	280 - 370	51 - 69	2,700	117"	--	--	--	--	60,000 - 100,000	MB80EXS
Okada	OKB318	6,401	5.9"	7,501	321 - 600	42.3 - 55.7	1,850 - 2,421	105"	--	--	--	--	62,000 - 94,001	OKB319
Okada	Top 300	6,448	6.1"	7,500	280 - 420	42.3 - 56.9	2,030 - 2,620	107"	--	--	--	--	62,000 - 94,000	Top 300
Atlas Copco	HB 3000	6,610	6.49"	--	280 - 540	55 - 71	2,320 - 2,611	116.1"	--	--	--	--	70,500 - 110,000	HB 3000
Chicago Pneumatic	CP 3050	6,614	6.5"	--	280 - 540	55 - 71	2,320 - 2,611	--	--	--	--	--	70,548 - 110,231	CP 3050
Indeco	HP 8000	6,650	6.30"	8,000	310 - 670	51 - 71	1,900 - 2,300	115.6"	--	--	--	--	60,000 - 110,000	HP 8000
BTI	VZ85	6,710	6.1"	8,500	380 - 650	50 - 69	2,030 - 2,755	128"	--	--	--	--	61,700 - 105,800	VZ85
NPK	GH-15	6,800	6.1"	8,000	320 - 400	53 - 66	2,600	130.75"	--	--	--	--	66,000 - 100,000	GH-15
Surestrike	1100	6,800	6"	20,000	16	30 - 35	2,700 - 3,000	276"	20,000	--	--	--	45,000	1100
Arrowhead	S330	6,855	6.30"	8,000	400 - 700	40 - 55	2,550	102"	--	--	--	--	60,000 - 110,000	S330
Construction Attachments	CAL8000-A	6,877	6.10"	8,000	230 - 600	47.6 - 84.5	1,860 - 2,580	127.2"	--	--	--	--	70,000 - 90,000	CAL8000-A
Allied Construction Products	G 90 C Sandvik (Rammer)	6,940	6.30"	7,500	300 - 480	55 - 82	2,030 - 2,180	117"	--	--	--	--	77,000 - 121,000	G 90 C Sandvik (Rammer)
Allied Construction Products	G 90 Pro Sandvik (Rammer)	6,940	6.30"	9,000	300 - 630	55 - 82	1,740 - 2,320	117"	--	--	--	--	77,000 - 121,000	G 90 Pro Sandvik (Rammer)
Caterpillar	H160Ds	6,946	6.3"	8,000	380 - 560	58 - 82	2,321	116.5"	3,956	--	--	--	70,400 - 121,000	H160Ds

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES MANAGER**  
Your guide to aggregates



## NOMINAL RATINGS CERTIFIED MEASUREMENTS

Make	Model	Tool diameter (in)	Working weight (lbs)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>7,000 to &lt;9,000 lbs working weight</b>														
BTI	BT8000	5.9"	7,012	8,000	280 - 400	48 - 66	2,031 - 2,611	128"	6,000	600	75.0	2,000	62,000 - 99,000	BT8000
Socomec	MDO 3200	6.5"	7,056	10,000	450 - 600	60.0 - 75.0	2,000	125.0"	6,451.7	260 - 400	52 - 68	2,000	66,000 - 100,000	MDO 3200
Maverick	10000	6.5"	7,110	10,000	260 - 400	52 - 68	2,275 - 2,702	--	4,024	--	--	--	79,000 - 110,000	10,000
Komac	TOR-42	6.10"	7,297	8,000	240 - 500	50.2 - 66.0	2,321 - 2,611	134"	--	--	--	--	75,000 - 104,000	TOR-42
FRD Furukawa	KF 45Qt	6.5"	7,507	8,000	300 - 500	50 - 66	2,320 - 2,610	129"	--	--	--	--	70,000 - 97,000	KF 45Qt
Tramac	V56MS	6.6"	7,563	12,000	330 - 1,045	63.4 - 85.3	2,394	115.1"	--	--	--	--	77,150 - 132,300	V56MS
NPK	GH-18	6.5"	7,800	12,000	300 - 400	58 - 77	2,500	136.25"	--	--	--	--	70,000 - 114,000	GH-18
Allied Construction Products	AR 170C	6.69"	7,815	11,000	300 - 400	55 - 74	1,900 - 2,200	127"	--	--	--	--	90,000 - 133,000	AR 170C
Atlas Copco	HB 3600	6.69"	7,940	--	280 - 560	63 - 79	2,320 - 2,610	--	--	--	--	--	77,200 - 138,900	HB 3600
UB Equipment	UB-319	6.9"	8,222	11,000	200 - 400	47.6 - 87.0	2,280 - 3,000	--	--	--	--	--	70,000 - 110,000	UB-319
Maverick	12,000	7.1"	8,267	12,000	260 - 400	55 - 76	2,275 - 2,702	--	7,095.3	260 - 400	55 - 76	2,650	90,000 - 140,000	12,000
BTI	TB2080XC	6.3"	8,326	10,000	450 - 550	75 - 92	2,030 - 2,755	130.4"	5,338	505	83	2,650	75,000 - 140,000	TB2080XC
Allied Construction Products	G 110 C Sandvik (Rammer)	6.89"	8,380	12,000	300 - 480	58 - 85	2,030 - 2,250	119"	--	--	--	--	88,000 - 154,000	G 110 C Sandvik (Rammer)
Allied Construction Products	G 110 Pro Sandvik (Rammer)	6.89"	8,380	12,000	300 - 700	58 - 92	1,740 - 2,395	119"	--	--	--	--	88,000 - 154,000	G 110 Pro Sandvik (Rammer)
Caterpillar	H180DS	6.69"	8,600	11,000	370 - 520	57 - 78	2,321	118.3"	4,357	--	--	--	132,000 - 166,000	H180DS
Stanley	MB 100EXS	6.9"	8,799	12,000	230 - 320	55 - 80	2,700	128"	--	--	--	--	80,000 - 130,000	MB 100EXS
Indeco	HP 10000	7.10"	8,900	10,000	320 - 580	67 - 81	2,050 - 2,350	126.2"	--	--	--	--	75,000 - 125,000	HP 10000

Certified measurements: Certified by the Association of Equipment Manufacturers.

# HYDRAULIC HAMMERS/BREAKERS CURRENT MAKES AND MODELS

**AGGREGATES  
MANAGER**  
Your guide to  
equipment



Make	Model	Working weight (lbs)	Tool diameter (in)	Energy impact class (ft-lbs)	Impact frequency range (blows/min)	Oil flow range (gpm)	Operating pressure range (psi)	Overall length with tool (in)	AEM tool energy rating (ft-lbs/blow)	AEM measured impact frequency (blows/min)	AEM measured oil flow (gpm)	AEM measured hydraulic pressure (psi)	Manufacturer's recommended carrier size range (lbs)	Model
<b>2,000 to &lt;12,000 lbs working weight</b>														
BTI	BT110000	9,233	6.5"	10,000	250 - 320	66 - 85	2,031 - 2,611	144"	-	-	-	-	88,000 - 132,000	BT110000
Chicago Pneumatic	CP 4250	9,259	7.1"	-	270 - 530	66 - 85	2,320 - 2,611	-	-	-	-	-	92,594 - 165,347	CP 4250
Atlas Copco	HB 4200	9,260	7.09"	-	270 - 530	66 - 84	2,320 - 2,610	125.15"	-	-	-	-	92,600 - 165,000	HB 4200
Okada	Top400	9,325	6.7"	10,000	320 - 400	74 - 92.6	2,030 - 2,620	120.6"	-	-	-	-	76,000 - 110,000	Top400
Construction Attachments	CAL11000-A	9,354	6.89"	11,000	230 - 550	68.7 - 105.7	2,150 - 2,570	143.7"	-	-	-	-	80,000 - 140,000	CAL11000-A
Komac	TOR-555	9,656	6.89"	11,000	210 - 450	55.5 - 81.9	2,321 - 2,756	140"	-	-	-	-	103,600 - 155,000	TOR-55
BTI	TB2580XC	10,195	7.0"	13,500	435 - 533	90 - 110	2,030 - 2,755	147"	-	-	-	-	99,000 - 180,000	TB2580XC
FRD Furukawa	KF 70 Qt	10,274	7.09"	10,000	250 - 320	66 - 90	2,320 - 2,610	148.5"	5,260	-	-	-	97,000 - 154,000	KF 70 Qt
Surestrike	2100	10,700	6"	28,600	20	30 - 35	2,700 - 3,000	276"	28,600	-	-	-	70,000	2100
Indeco	HP 12000	11,100	7.70"	12,000	270 - 540	77 - 94	2,050 - 2,350	132.5"	-	-	-	-	86,000 - 170,000	HP 12000
UB Equipment	UB-321	11,536	7.3"	13,500	200 - 360	58.0 - 103.0	2,400 - 3,130	-	-	-	-	-	110,000 - 140,000	UB-321
Okada	OKB 330	11,905	7.3"	15,000	260 - 340	74 - 100	1,990 - 2,630	138"	-	-	-	-	100,000	OKB 330

**Certified measurements:** Certified by the Association of Equipment Manufacturers.



## MANUFACTURERS INDEX

### **Allied Construction Products, LLC**

3900 Kelley Ave.  
Cleveland, OH 44114  
216-431-2600  
800-321-1046  
216-431-2601 fax  
[www.alliedcp.com](http://www.alliedcp.com)

### **Arrowhead Rockdrill Co., Inc.**

1550 State St.  
Barstow, CA 92311  
760-255-8990  
800-984-3222  
760-255 8980 fax  
[www.arrowheadrockdrill.com](http://www.arrowheadrockdrill.com)

### **Atlas Copco Construction Equipment**

3700 E. 68th Ave.  
Commerce City, CO 80022  
303-287-2802  
800-760-4049  
800-952-7975 fax  
[www.atlascopco.us](http://www.atlascopco.us)

### **BTI (Breaker Technology)**

35 Elgin St.  
Thornbury, ON, Canada N0H 2P0  
519-538-2189  
519-599-6803  
[www.rockbreaker.com](http://www.rockbreaker.com)

### **Caterpillar Inc.**

100 N.E. Adams St.  
Peoria, IL 61629  
309-675-1000  
309 675-4757 fax  
[www.cat.com](http://www.cat.com)

### **Chicago Pneumatic**

3700 E. 68<sup>th</sup> Ave.  
Commerce City, CO 80022  
800-760-4049  
800-952-7975 fax  
[www.cp.com](http://www.cp.com)

### **Construction Attachments**

1160 Cal Ct.  
Lenoir, NC 28645  
828-758-2674  
800-255-4461  
828-754-1887 fax  
[www.calmfg.com](http://www.calmfg.com)

### **Indeco North America**

135 Research Dr.  
Milford, CT 06460  
203-713-1030  
800-542-6637  
203-713-1040 fax  
[www.indeco-breakers.com](http://www.indeco-breakers.com)

### **FRD Furukawa (formerly Kent Demolition Tools)**

711 Lake St.  
Kent, OH 44240  
330-673-5826  
800-527-2282  
330-677-1616 fax  
[www.kentdemolition.com](http://www.kentdemolition.com)

### **Komac America**

9009 Freeway Dr., Ste. 1  
Macedonia, OH 44056  
330-468-0833  
330-468-0847 fax  
[www.komac.co.kr](http://www.komac.co.kr)

### **Maverick Equipment Mfg. (Maverick Hammers)**

31 Graystone St.  
Warwick, RI 02886  
401-738-6800  
800-618-7628  
401-244-5899 fax  
[www.maverickhammers.com](http://www.maverickhammers.com)

### **NPK**

7550 Independence Dr.  
Walton Hills, OH 44146  
440-232-7900  
800-225-4379  
440-232-4382 fax  
[www.npkce.com](http://www.npkce.com)

### **Okada America**

904 Medina Rd.  
Medina, OH 44256  
330-239-2666  
800-270-0600  
330-239-3670 fax  
[www.okadaamerica.com](http://www.okadaamerica.com)

### **Socomec**

439 Rte. 17 North  
Mahwah, NJ 07430  
201-236-0969  
888-762-6632  
201-584-0229 fax  
[www.eei-us.com](http://www.eei-us.com)

### **Stanley Hydraulic Tools**

3810 S. E. Naef Rd.  
Milwaukie, OR 97267-5698  
503-659-5660  
800-972-2647  
503-652-1780 fax  
[www.stanley-hydraulic-tools.com](http://www.stanley-hydraulic-tools.com)

### **Surestrike**

P.O. Box 358  
Luck, WI 54853  
715-472-8844  
866-472-8844  
715-472-8845 fax  
[www.surestrike.biz](http://www.surestrike.biz)

### **Tramac**

1293 Glenway Dr.  
Statesville, NC 28625  
866-472-4373  
866-472-4950  
[www.tramacUS.com](http://www.tramacUS.com)

### **UB Equipment**

4701 Littlejohn St.  
Baldwin Park, CA 91706  
626-813-1591  
800-813-8232  
626-813-1594 fax  
[www.ubequipment.com](http://www.ubequipment.com)